

AIRMAIL/ SPEED POST

Our Ref: FMCD/CM/L-4100361273

Dated: 12-10-2026

Subject: Grant of BIS Product Certification Licence No. - 4100361273 as per IS 9550 : 2024

M/s BGH Edelstahl Freital GmbH
Am Stahlwerk 1, 01705 Freital –
Germany 01705

Dear Madam(s)/Sir(s),

With reference to your application A-4106344, we are pleased to inform you that the Certification Marks Licence has been granted to you to use the Standard Mark in respect of the followings:

Name of the Product	Bright Steel Bars
Product Designation	As Per Annex -I
Treatment Condition at Delivery	
Product Form	Round
Surface Quality Class	Class 3
Sizes	From 14.0 mm up to and including 165 mm Tolerance class : h9 to h12, as per customer requirement

IS 9550 : 2024

2. The number assigned to this Licence is CM/L- 4100361273 which has been made operative from 14-09-2026 and is valid up to 13-09-2029. This licence is granted for 3 years with applicable fee deposition of one year only. Requisite fee is required to be submitted annually with details as given at para 6, 7 and 8 of this letter. The licence number shall invariably be referred to in your future correspondence.

3. The licence is granted on the explicit condition that you should mark entire production under scope of licence with Standard Mark and maintain conformity to the relevant Indian Standards. In addition, you should display the BIS product certification licence held by you prominently at your premises and also mention the BIS product certification licence held by you in your commercial advertisements.

4. According to Sub-Paragraph (1) & (3) of Paragraph 5 of Scheme-I of Schedule-II under Bureau of Indian Standards (Conformity Assessment) Regulations, 2018, the **annual licence fee of Rs 1000.00** and the **marking fee of Rs. 83000.00** for use of Standard Mark as per Annexure-I of Scheme-I of BIS (Conformity Assessment) Regulations, 2018 is payable by you **with effect from 14-09-2026** for the period of validity of licence in advance.

5. Minimum Marking fee stipulated under Scheme-I of BIS (Conformity Assessment) Regulations, 2018 is payable by you regardless of the fact whether you actually mark your product or not with the Standard Mark. **Our Receipt No. HQNDNT2025001967 dated 14-09-2026** for the licence fee and the minimum marking fee for the first operative period is already enclosed.

6. This advance minimum marking fee will be carried over to the next year on every occasion. The actual marking fee calculated on the unit rate on the production marked or the minimum marking fee, whichever is higher, shall be payable by you annually before completion of one year period. Production statement is required to be furnished by you for calculation of actual marking fee.

7. With a view to streamlining the reporting of quantity marked, calculation and collection of marking fee on the unit rate basis, fees will be calculated on the production marked during the first nine months of operation of the licence. After first year, production marked during twelve months comprising the last three months of the previous operative year and the first nine months of the current operative year will be taken for calculation of actual marking fees. In case the licence gets cancelled or expires, the entire production marked till the cancellation or expiry date shall be taken into account for calculating the marking fee payable.

8. If the production statement and/or annual fees is not received within timelines (i.e. before completion of the one year period), then the licence shall stand suspended or deferred for 90 days duration. During the period of these 90 days, the requisite information with fee accompanied with late fee of ₹ 5,000 can be submitted to make the licence operative. Otherwise, the licence shall stand cancelled or expired.

9. The Quality Assurance Plan (QAP) submitted by you and agreed by BIS or the Scheme of Inspection and Testing as specified by BIS* will have to be implemented by your organisation strictly and completely. This supervision of the operation of the Scheme shall be done by a person responsible for the quality control function in your organisation. Kindly inform us the name and designation of the person who will be held responsible for the operation and maintenance of the Scheme. Any future change in this respect will have to be communicated by you to us as and when these take place.

10. We are enclosing a sheet giving the preferred dimensions of the Standard Mark to enable you to prepare the designs of the Standard Mark for marking the above product Photographic reduction in any size is permissible. This will ensure the relative proportions of the different dimensions maintained. Preferred dimensions be used as far as possible.

11. On commencement of marking of your product for which you are licensed, you may advertise your product with Standard Mark in various media only during the validity of your licence. The use of Standard Mark on letterheads and publicity literature will be permitted only on receipt of your assurance that in the event of cancellation or lapsing of your licence, the Standard Mark on your letterheads, publicity literatures etc. will be destroyed/obliterated.

12. This licence is granted for your manufacturing premises situated at **Am Stahlwerk 1, 01705 Freital – Germany 01705** Privileges under the licence shall not be exercised by any other firm company/factory etc. This licence is not transferable in the event of shifting the manufacturing and testing equipment from the licensed premises to some other place, use of Standard Mark shall be stopped till the new premises are inspected and found to be satisfactory by BIS in respect of manufacturing and testing facilities available there and the address of the new premises is endorsed in the licence.

13. You are also advised to make yourself and other employees in your organisation aware about the provisions of the BIS Act, 2016 and Rules and Regulations framed thereunder especially the implications in case of any intentional or unintentional non-adherence.

14 You are requested to furnish the Agreement for grant of licence, duly executed on a **non-judicial stamp papers of Rs.100.00**, incorporating the terms and conditions of the BIS certification marks licence granted to you, as per the format enclosed with 15 days of issue of the letter.

14. You are required to furnish a **Bank Guarantee for USD 10,000 (US Dollars ten Thousand only)** having validity of six months more than the validity of the licence issued by any Bank to the satisfaction of BIS by way of performance security Bond for due compliance of the provisions of the BIS Act, 2016, the Rules and Regulations framed thereunder, and the terms and conditions of this agreement, as per format enclosed herewith within 45 days of issue of this letter.

15. You are also required to submit an **Indemnity Bond** to declare BIS harmless and indemnified in respect of any third-party claims with regard to conformity of your products to the correspondence Indian Standards under the afore-mentioned BIS licence granted to you, as per format enclosed herewith within 15 days of issue of this letter.


16. Kindly acknowledge receipt of this letter.

Notes: (1) Performance Bank Guarantee (PBG) (para 14 above) shall be issued by any Bank having RBI approved branch in INDIA. Original PBG shall be endorsed & routed / forwarded through the Indian branch.

(2) Kindly note that if the time norms indicated in para 13, 14, and 15 above are not complied with, BIS may be constrained to take actions as per norms including stoppage of marking for the licence.

Thanking you,

Signature of designated authority




(Manish Kumar)
Sc. F & Head (FMCD)

Encl: As above.

Copy to: Mr. BalasubramanianThiyagarajan
No. 56, 5th Main 6th Cross RPC Layout,
Vijayanagar, Bengaluru – 560040,
Karnataka, India

Annex-I to the scope of the licence
(A-4106344 as per IS 9550 : 2024)

Product Designation	Chemical Composition %	Treatment condition at delivery	Mechanical Properties
Steel Group: Stainless Steel, Sub- Category: Martensitic			
IS 9550 1.4415 X2CrNiMo13-5-2 / S13Cr	C: 0.030 Max, Si: 0.50 Max, Mn: 0.70 Max, P: 0.04 Max, S: 0.015 Max, Cr: 11.5 to 13.5, Ni: 4.5 to 6.5; Mo: 1.5 to 2.5	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 1.4923 X22CrMoV12-1	C: 0.18 to 0.24, Si: 0.1 to 0.50, Mn: 0.4 to 0.80, P: 0.025 Max, S: 0.015 Max, Cr: 11.0 to 12.5, Mo: 0.80 to 1.20, Ni: 0.30 to 0.80, V: 0.25 to 0.35, Al: 0.040 Max, Ti: 0.050 Max, B: 0.0015 Max	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 1.4903 X10CrMoVNb9-1 AISI F91	C: 0.08 to 0.12, Si: 0.50 Max, Mn: 0.30 to 0.60, P: 0.020 Max, S: 0.005 Max, Al: 0.040 Max, Cr: 8.0 to 9.5, Mo: 0.85 to 1.05, Ni: 0.30 Max, V: 0.18 to 0.25, Nb: 0.06 to 0.10, N: 0.030 to 0.070, Cu: 0.30 Max	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 1.4913 X19CrMoNbVN11-1	C: 0.17 to 0.23, Si: 0.50 Max, Mn: 0.40 to 0.90, P: 0.025 Max, S: 0.015 Max, Al: 0.020 Max, B: 0.0015 Max, Cr: 10.0 to 11.5, Mo: 0.50 to 0.80, Ni: 0.20 to 0.60, V: 0.10 to 0.30, Nb: 0.25 to 0.55, N: 0.05 to 0.10	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 1.4922 X20CrMoV11-1	C: 0.17 to 0.23, Si: 0.40 Max, Mn: 0.30 to 1.00, P: 0.025 Max, S: 0.015 Max, Cr: 10.0 to 12.5, Mo: 0.80 to 1.20, Ni: 0.30 to 0.80, V: 0.20 to 0.35	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 CPS 14331 X21Cr12Mo1V3 1.4923 X22CrMoV12-1	C: 0.18 to 0.24, Si: 0.1 to 0.50, Mn: 0.4 to 0.80, P: 0.025 Max, S: 0.015 Max, Cr: 11.0 to 12.5, Mo: 0.80 to 1.20, Ni: 0.30 to 0.80, V: 0.25 to 0.35	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 1.4935 X20CrMoWV12-1 Grade 616 AISI 422/ S42200	C: 0.20 to 0.25, Si: 0.20 to 0.50, Mn: 0.50 to 1.00, P: 0.025 Max, S: 0.025 Max, Cr: 11.0 to 12.5, Mo: 0.90 to 1.25, Ni: 0.50 to 1.00, V: 0.20 to 0.30, W: 0.90 to 1.25, Al: 0.05 Max, Ti: 0.05 Max, Sn: 0.05 Max	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 1.4938 X12CrNiMoV12-3	C: 0.08 to 0.15, Si: 0.50 Max, Mn: 0.40 to 0.90, P: 0.025 Max, S: 0.015 Max, Cr: 11.0 to 12.5, Mo: 1.50 to 2.00, Ni: 2.00 to 3.00, V: 0.25 to 0.40, N: 0.020 to 0.040	+QT (quenched and tempered)	HBW: 350 Max
Steel Group: Stainless Steel, Sub- Category: Austenitic			
IS 9550 1.4980 X6NiCrTiMoVB25-15-2 Grade 660	C: 0.08 Max, Si: 1.00 Max, Mn: 2.00 Max, P: 0.040 Max, S: 0.030 Max, Cr: 13.5 to 16.0, Mo: 1.00 to 1.50, Ni: 24.0 to 27.0, V: 0.10 to 0.50, Al: 0.35 Max, Ti: 1.90 to 2.35, B: 0.001 to 0.010	+AT+P (Solution annealed & age hardened)	HBW: 350 Max
IS 9550 1.4828 X15CrNiSi20-12	C: 0.20 Max, Si: 1.50 to 2.50, Mn: 2.00 Max, P: 0.045 Max, S: 0.015 Max, Cr: 19.00 to 21.00, Ni: 11.00 to 13.00, N: 0.11 Max	+AT (solution annealed)	HBW: 350 Max
Steel Group: Alloy Steel, Sub- Category: Low alloy			
IS 9550 1.5415 16Mo3	C: 0.12 to 0.20, Si: 0.35 Max, Mn: 0.40 to 0.90, P: 0.025 Max, S: 0.010 Max, Cr: 0.30 Max, Mo: 0.25 to 0.35, Ni: 0.30 Max, Cu: 0.30 Max, N: 0.012 Max	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 CPS 14331 1.7227 42CrMoS4	C: 0.38 to 0.45, Si: 0.40 Max, Mn: 0.6 to 0.9, P: 0.025 Max, S: 0.02 to 0.04, Cr: 0.9 to 1.2, Mo: 0.15 to 0.3	+QT (quenched and tempered)	HBW: 375 Max
IS 9550 1.7228 50CrMo4	C: 0.45 to 0.55, Si: 0.40 Max, Mn: 0.5 to 1.0, P: 0.025 Max, S: 0.025 Max, Cr: 0.90 to 1.20, Mo: 0.15 to 0.30, Cu: 0.40 Max	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 1.7335 13CrMo4-5	C: 0.08 to 0.18, Si: 0.35 Max, Mn: 0.4 to 1.0, P: 0.025 Max, S: 0.010 Max, Cr: 0.70 to 1.15, Mo: 0.40 to 0.60, Ni: 0.30 Max, Cu: 0.30 Max, N: 0.012 Max	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 1.7380 10CrMo9-10	C: 0.08 to 0.14, Si: 0.50 Max, Mn: 0.4 to 0.80, P: 0.020 Max, S: 0.010 Max, Cr: 2.00 to 2.50, Mo: 0.90 to 1.10, Cu: 0.30 Max, N: 0.012 Max	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 CPS 14331 21Cr5Mo7V3 1.7709 21CrMoV5-7	C: 0.17 to 0.25, Si: 0.15 to 0.35, Mn: 0.35 to 0.85, P: 0.03 Max, S: 0.035 Max, Cr: 1.2 to 1.5, Mo: 0.65 to 0.8, V: 0.25 to 0.35	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 CPS 14331 40Cr4Mo6V3 1.7711 40CrMoV4-6	C: 0.36 to 0.44, Si: 0.15 to 0.35, Mn: 0.35 to 0.85, P: 0.03 Max, S: 0.035 Max, Cr: 0.9 to 1.2, Mo: 0.6 to 0.75, V: 0.25 to 0.35	+QT (quenched and tempered)	HBW: 450 Max
IS 9550 1.7729 20CrMoVTiB4-10	C: 0.17 to 0.23, Si: 0.35 Max, Mn: 0.5 Max, P: 0.030 Max, S: 0.03 Max, Cr: 0.90 to 1.40, Mo: 0.80 to 1.10, Ni: 0.50 Max, V: 0.70 to 1.0, Ti: 0.05 to 0.12, B: 0.005 Max	+QT (quenched and tempered)	HBW: 350 Max
IS 9550 1.8519 31CrMoV9	C: 0.27 to 0.34, Si: 0.4 Max, Mn: 0.40 to 0.70, P: 0.025 Max, S: 0.035 Max, Cr: 2.3 to 2.7, Mo: 0.15 to 0.25, V: 0.10 to 0.20	+QT (quenched and tempered)	HBW: 375 Max


12/10/2024